

Package ‘mFDP’

October 13, 2022

Type Package

Title Flexible Control of the mFDP

Version 0.1.0

Date 2022-08-19

Maintainer Jesse Hemerik <jesse.hemerik@wur.nl>

Description Computes bounds for the median of the false discovery proportion (mFDP).

These 50 percent confidence bounds for the FDP are simultaneously valid.

The method takes a vector of p-values as input. Also provides mFDP-adjusted p-values.

Can be used for flexible mFDP control.

License GNU General Public License

Imports methods

NeedsCompilation no

Author Jesse Hemerik [aut, cre]

Repository CRAN

Date/Publication 2022-08-22 14:30:05 UTC

R topics documented:

get.bound	1
get.kappa.max	2
mFDP.adjust	3

Index

5

get.bound	<i>Compute a 50 percent confidence upper bound for the number of false positives</i>
-----------	--

Description

For a p-value rejection threshold t , compute the 50 percent confidence upper bound for the number of false positives. The bounds are simultaneous over t .

Usage

```
get.bound(t,c,kappa.max)
```

Arguments

t	The p-value threshold
c	The tuning parameter, which influences the intercept and slope of the enveloppe. Should be numeric.
kappa.max	This value needs to be computes based on the p-values. Together with c it defines the bounds.

Value

A non-negative integer, which is a median unbiased (or upward biased) estimate of the number false positives.

Examples

```
#Suppose the envelope that has been computed is defined by c=0.002 and kappa.max=0.001.
#We can then evaluate the envelope at several thresholds t as below.
#This is equivalent to simply entering the formula floor((t+c)/kappa.max).

#50 percent confidence upper bound for nr of false positives, if p-value threshold of 0.01 is used:
get.bound(t=0.01,c=0.002,kappa.max=0.001) #12

#50 percent confidence upper bound for nr of false positives, if p-value threshold of 0.02 is used:
get.bound(t=0.02,c=0.002,kappa.max=0.001) #22

#50 percent confidence upper bound for nr of false positives, if p-value threshold of 0.03 is used:
get.bound(t=0.03,c=0.002,kappa.max=0.001) #32
```

get.kappa.max

Based on a vector of raw p-values, compute kappa.max, which defines the mFDP envelope

Description

Based on a vector of unadjusted(!) p-values, compute kappa.max, which together with c defines the mFDP envelope

Usage

```
get.kappa.max(P, c="1/(2m)", s1=0, s2=0.1)
```

Arguments

- P A vector of p-values.
- c The tuning parameter, which influences the intercept and slope of the enveloppe. Should either be numeric or " $1/(2m)$ " or " $1/m$ ".
- s1 The smallest p-value threshold of interest. Non-negative.
- s2 The largest p-value threshold of interest. Should be larger than s1 and at most 1.

Value

`kappa.max`, which together with c defines the mFDP envelope.

Examples

```
set.seed(5193)

### Make some p-values
m=500      #the nr of hypotheses
nrfalse=100 #the nr of false hypotheses

tstats = rnorm(n=m)  #m test statistics
tstats[1:nrfalse] = tstats[1:nrfalse] + 3    #add some signal
P = 1 - pnorm(tstats)                         #compute p-values

### Compute kappa.max. (Taking c to be the default value  $1/(2m)$ .)
kappa.max = get.kappa.max(P=P)
kappa.max
```

`mFDP.adjust`

compute mFDP-adjusted p-values

Description

Provides mFDP-adjusted p-values, given a vector of p-values.

Usage

```
mFDP.adjust(P, c="1/(2m)", s1=0, s2=0.1)
```

Arguments

- P A vector of (raw, i.e. unadjusted) p-values.
- c The tuning parameter, which influences the intercept and slope of the envelope. Should either be numeric or " $1/(2m)$ " or " $1/m$ ".
- s1 The smallest p-value threshold of interest.
- s2 The largest p-value threshold of interest.

Value

A vector of mFDP-adjusted p-values. Some can be infinity - which can be interpreted as 1.

Examples

```
set.seed(5193)

### make some p-values
m=500          #the nr of hypotheses
nrfalse=100   #the nr of false hypotheses

tstats = rnorm(n=m)    #m test statistics
tstats[1:nrfalse] = tstats[1:nrfalse] + 3    #add some signal
P = 1 - pnorm(tstats)           #compute p-values

P.adjusted = mFDP.adjust(P=P)    #mFDP-adjusted p-values. Be careful with interpretation.

min(P.adjusted) #0.0208
```

Index

`get.bound`, [1](#)
`get.kappa.max`, [2](#)
`mFDP.adjust`, [3](#)